

Sat composteur

Objectif

surveiller la température du compost.

☐ Plages de température typiques dans un composteur

Phase	Température	Description
☐ Phase mésophile	10 °C à 40 °C	Début de la décomposition, activité modérée.
☐ Phase thermophile	40 °C à 70 °C	Période très active : dégradation rapide, stérilisation naturelle.
☐ Refroidissement	< 40 °C	Fin de l'activité intense, maturation du compost.
☐ Trop froid	< 10 °C	Compost "endormi", activité microbienne quasi nulle.
☐ Trop chaud	> 70 °C	Risque de tuer les micro-organismes bénéfiques ; pas souhaitable.

Hardware

- micro-contrôleur : ESP32C3 de chez Seeed (seeed_xiao_esp32c3)
- 2 [sondes de température DS18B20](#)

Yaml ESPHome

[composteur.yaml](#)

```
substitutions:
  devicename: composteur
  friendly_devicename: Composteur

esphome:
  name: ${devicename}
  friendly_name: ${friendly_devicename}

esp32:
  variant: ESP32C3
  board: seeed_xiao_esp32c3
  framework:
    type: arduino

# Enable logging
logger:
  # level: VERY_VERBOSE
```

```
# Enable Home Assistant API
api:
  encryption:
    key: "0987PÉUIÈ!VDLJ

ota:
  - platform: esphome
    password: "09rstceiupdl09876543ldvop"

wifi:
  ssid: !secret wifi_ssid
  password: !secret wifi_password

  # Enable fallback hotspot (captive portal) in case wifi connection
  fails
  ap:
    ssid: "${devicename} Fallback Hotspot"
    password: "09P009546XYP"

captive_portal:

one_wire:
  # D6
  - platform: gpio
    pin: GPIO21
    id: bus_ds18b20_1

  # D7
  - platform: gpio
    pin: GPIO20
    id: bus_ds18b20_2

sensor:
  - platform: dallas_temp
    one_wire_id: bus_ds18b20_1
    name: "Température 1 (${devicename})"
    resolution: 12
    update_interval: 60s

  - platform: dallas_temp
    one_wire_id: bus_ds18b20_2
    name: "Température 2 (${devicename})"
    resolution: 12
    update_interval: 60s

  - platform: wifi_signal
    name: "signal WiFi (${devicename})"
    update_interval: 60s

  - platform: uptime
```

```
name: "${devicename} Uptime Sensor"
id: ${devicename}_uptime_sensor
update_interval: 60s
on_raw_value:
  then:
    - text_sensor.template.publish:
        id: ${devicename}_uptime_human
        state: !lambda |-
            int seconds =
round(id(${devicename}_uptime_sensor).raw_state);
            int days = seconds / (24 * 3600);
            seconds = seconds % (24 * 3600);
            int hours = seconds / 3600;
            seconds = seconds % 3600;
            int minutes = seconds / 60;
            seconds = seconds % 60;
            return (
                (days ? String(days) + "j " : "") +
                (hours ? String(hours) + "h " : "") +
                (minutes ? String(minutes) + "m " : "") +
                (String(seconds) + "s")
            ).c_str();


text_sensor:
  - platform: wifi_info
    ip_address:
      name: "adresse IP (${devicename})"
      id: ${devicename}_ip_address

  - platform: template
    name: "Uptime (${devicename})"
    id: ${devicename}_uptime_human
    icon: mdi:clock-start

  - platform: version
    name: "Version d'ESPHome installée"
    id: ${devicename}_ESPHome_Version
```

Intégration Home Assistant

Panneau de contrôle



Code pour jauge température

[jauge.yaml](#)

```
type: gauge
entity: sensor.composteur_temp_rature_1_composteur
min: 5
max: 80
severity:
  green: 10
  yellow: 40
  red: 65
needle: true
name: Compartiment 1
```

Code pour courbes de températures

[courbes.yaml](#)

```
chart_type: line
period: 5minute
type: statistics-graph
entities:
  - sensor.composteur_temp_rature_1_composteur
  - sensor.composteur_temp_rature_2_composteur
stat_types:
```

- mean
- min
- max

From:

<https://wiki.lebiklab.fr/> - **Wiki Le BIK'LAB**

Permanent link:

<https://wiki.lebiklab.fr/doku.php?id=projets:home-assistant:aquaponie:sat-composteur&rev=1748127829>

Last update: **24/05/2025 23:03**

